

CompactFlash Cards



PCD-100A

CompactFlash Card

- 100% IDE compatible
- Endurance: 300,000 erase/program cycles per logical sector
- Memory Capacity: 8/16/32/48/64/96/128 MB
- Acoustic Noise: 0 dB (@1 meter)
- Performance: Data transfer rate to/from Flash: 40 Mbyte/sec burst
Data transfer rate to/from Host: 6.0 Mbyte/sec burst
Data reliability: <1 non-recoverable error in 1014 bits read
- P/N: PCD-100A

CompactPCI Enclosures 1

CompactPCI Boards 2

CompactPCI Peripherals 3

Blade Servers 4

Network Appliances 5

e-Server Systems 6

Storage Subsystems 7

Industrial Computer Chassis 8

Full-sized CPU Cards 9

Passive Backplanes 10

Industrial Computer Peripherals 11



PCD-250A/350A

2.5"/3.5" IDE Flash Drive

- Up to 384/896 MB of solid-state storage
- 100% IDE compatible
- Noiseless, Rugged & Light
- Automatic error correction and retry capabilities
- Sophisticated defect management system
- P/N: PCD-250A
PCD-350A



PCD-1240V/PCD-1244H

40/44 pin IDE Flash SSD

- Supports ATA/Ture IDE interfaces standard
- Low profile, 40-pin stand vertically and 44-pin horizontally
- Data transfer rate = 16.6 Mbytes/sec (P104 data transfer)
- ECC detects and corrects data errors automatically
- Supports Master/Slave setting
- Power supply requirement: Input voltage 3.3 V/5 V \pm 10%
- Capacity: 8/16/32 MB
- P/N: PCD-1240V
PCD-1244H

For More Information

www.advantech.com/nc

Enter

ADVANTECH

• All brand names and registered trademarks are the property of their respective owner
• All specifications are subject to change without notice

Date of Publication: 2003-07-14