

# MIC-3390

## 6U CompactPCI® Intel® Pentium® M Processor-based Board with Dual PCIe GbE/DDR2/SATA/PMC



### Features

- Supports low-power Intel® Pentium® M processor at up to 2.0 GHz in a 479-pin Micro-FCPGA socket
- PCI Express dual Gigabit Ethernet on board
- Dual channel DDR2 400/533 MHz SDRAM up to 2 GB
- PICMG 2.16 R1.0 CompactPCI® Packet Switching Backplane Specification compliant
- PICMG 2.9 R1.0 CompactPCI System Management Specification compliant
- PICMG 2.1 R2.0 CompactPCI Hot Swap Specification compliant
- Onboard SATA 2.5" HDD bay, PMC connector and CompactFlash socket

### Introduction

The MIC-3390 single board computer is designed to offer embedded system builders the best value in low-power Intel Pentium M computing. The Intel Pentium M processor, Mobile Intel 915GM Express chipset and Intel I/O Controller Hub ICH6M, enables the MIC-3390 to deliver great computing performance, connectivity and throughput without compromising system thermal design. The MIC-3390 Graphic Memory Controller Hub and ICH6M provide an optimized integrated memory, graphics and I/O solution. The MIC-3390 is validated for all Intel Pentium M processors, and supports up to 2 GB of 400/533 MHz DDR2 memory in dual-channel SODIMMs.

The MIC-3390 maximizes I/O throughput with the ICH6-M's PCI Express (PCIe) ports. The two Intel 82573E Ethernet controllers are linked directly using PCIe connectivity for a total bidirectional peak bandwidth of 2 Gb/s. Another PCIe lane connects to a PCIe to PCI-X Bridge to provide a 64-bit / 100 MHz data path for the PMC and a 64-bit / 66 MHz data path for the CompactPCI Bridge. The flexibility of the bridge allows the MIC-3390 to be used in a system slot or a peripheral slot as an intelligent I/O processor or as an application blade in a multi-processor or clustered architecture. In addition to a full array of industry standard I/O features, ICH6M provides two Serial ATA ports for high speed data transfers up to 150 MB/s. One port is routed to rear I/O and the other port is routed to both the onboard 2.5" SATA drive and rear I/O for a greater choice of connectivity. With an optional mezzanine card, the MIC-3390 provides a fully compatible IPMI 2.0 interface with LAN and serial port support for out-of-band management.

### Specifications

Processor System	CPU (Not Included)	Intel Pentium M Processor (Socket 479)
	Max. Speed	2.0 GHz (2 MB L2 cache)
	Chipset	Intel 915GM
	BIOS	Award™ 4 Mbit flash
Bus	Front Side Bus	400/533 MHz
	PCI	Up to 64-bit/100 MHz (PCI-X support)
Memory	Technology	DDR2 400/533 MHz SDRAM
	Max. Capacity	2 GB
	Socket	SODIMM x 2
Graphic	Controller	Integrated in Intel 915GM
	VRAM	Dynamic
	Resolution	Up to 2048 x 1536, 64k color at 75 Hz
Ethernet	Interface	10/100/1000Base-TX Ethernet
	Controller	Intel 82573E x 2
	I/O Connector	RJ-45 x 2 (front)
Storage	Mode	SATA
	Channels	2
	Storage Site	One SATA connector and space reserved for embedded 2.5" HDD
Bridge	Bus	PCI 64-bit/66 MHz
	Interface	Universal (System/Peripheral mode capability)
I/O Interface	Serial (COM1)	RJ-45 x 1 (front)
Operating System	Compatibility	Windows® XP/2000/NT 4.0, Red Hat Fedora Core 3
Hardware Monitor	Controller	Winbond W83782D
	Monitor	CPU temperature, +3.3 V, +5 V, +12 V
Watchdog Timer	Output	Interrupt, system reset, NMI
	Interval	Programmable, 0 ~ 255 sec.
PMC	Site	1
	Interface	PCI Mezzanine (IEEE1386.1 compliant)
	Signal	+5 V/+3.3 V compliant

## Specifications Cont.

Miscellaneous	Solid State Disk	One CompactFlash socket			
	LED Indicator	HDD, Power, Hot swap			
	USB 2.0	2 channels			
	Real Time Clock	Built-in			
Power Requirement (Intel 1.8 GHz with 1 GB memory)	Voltage	+3.3 V	+5 V	+12 V	-12 V
	Typical	4 A	4 A	< 12 mA	< 65 mA
	Maximum	4.2 A	6.2 A	< 20 mA	< 57 mA
Physical Characteristics	Dimensions (W x D)	233.35 x 160 mm (9.19" x 6.3"), 1-slot width			
	Weight	0.8 kg (1.76 lb)			
Environment	Temperature	Operating 0 ~ 65° C (32 ~ 149° F)		Non-Operating -40 ~ 70° C (-40 ~ 140° F)	
	Humidity	-		95% @ 60° C (non-condensing)	
	Shock	20 G		50 G	
	Vibration (5 ~ 500 Hz)	1.5 Grms		2.0 G	
	Altitude	60 m below sea level to 4000 m above sea level			
	Airflow	300 LFM=1.54 m/s			
Regulatory	Conformance	FCC Class A, CE			
	NEBS Level 3	Design for GR-63-core & GR-1089-core			
Compliance	PICMG 2.0 R3.0 CompactPCI Specification PICMG 2.1 R2.0 CompactPCI Hot Swap Specification PICMG 2.9 R1.0 CompactPCI System Management Specification PICMG 2.16 R1.0 CompactPCI Packet Switching Backplane Specification				

## Recommended Configurations

CPU Board	PMC Module	Rear I/O Board	Enclosure
MIC-3390E, MIC-3390-AE	MIC-3665-AE, MIC-3665-BE	RIO-3310AE, RIO-3310S-A1E, RIO-3310S-A2E	MIC-3039-B, MIC-3042, MIC-3043, MIC-3081B, MIC-3056, MIC-3041, CP-150 series

## Rear Transition Board


Part Number	Rear Panel							Onboard Header/Socket/Connector							Slot Width	
	KB & Mouse	COM2*	GbE LAN	VGA	USB	10/100Base-T LAN	SCSI**	IDE	SATA	FDD	COM1	SCSI**	PRT	USB		Conn.
RIO-3310AE	1	1	2	1	1	1	-	1	1	1	1	-	1	1	J3/J5	1
RIO-3310S-A1E	1	1	2	1	1	1	-	1	1	1	1	1	1	1	J3/J5	1
RIO-3310S-A2E	1	1	2	1	1	1	1	1	1	1	1	1	1	1	J3/J5	1

\* Optional 3rd LAN port occupies the rear COM2 port

\*\* Internal Ultra 320 SCSI port with optional external rear I/O port

## Ordering Information

Part Number	Front Panel I/O					Main Onboard Features					
	LAN	COM	PMC	USB	VGA	CPU	Memory	CF Socket	IDE Channel	Slot Width	IPMI BMC Module
MIC-3390E	2	1	1	2	1	-	-	1	2.5" SATA HDD	1	-
MIC-3390-AE	2	1	1	2	1	-	-	1	2.5" SATA HDD	1	1



One CompactFlash socket  
Two DIMM sockets

One 64-bit/66 MHz PMC connector

One passive CPU heat sink



One PMC knockout  
Two USB 2.0 ports  
One RJ-45 COM1 port

Two RJ-45 Gigabit LAN ports  
One DB-15 VGA port